



Order No. 5.42010 Water Scoop

### Play value

This equipment is a nicely shaped water scoop where children can play and observe the flowing characteristics of water. When the wheel is turned around, water is drawn from the basin. The water then pours into the channels on both sides. It is directed by the channels into the flow dish and is redirected from there into the basin through a water outlet pipe. The water quantity coming into the channels varies with relation to the rotating speed of the wheel. The water can, for example, flow from both sides into the dish so that a constantly changing flow configuration results.

### Fundamental characteristics

- Special technical solution for water intake and distribution
- Awarded design
- Through water flow from both sides, special flow configurations can be observed
- The Scooping Wheel can also be combined with other water play systems
- Unique and original
- Incentive for playing: big wheel

### Recommended for

- Kindergarten children
- School children
- Public play areas without supervision, such as playgrounds, parks or similar
- Swimming pools without supervision, such as outdoor pools, adventure pools or similar


### Barrier-free

- Independent play




Order No. 5.20880 Scooping Wheel, Photo © Daniel Perales


### Scooping Wheel Water Scoop



5.20880



5.42010



## Technical information

Equipment made of stainless steel, glass bead blasted

## Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



**For more detailed explanation of the quality characteristics see price list.**

Easy drive in maintenance free plastic bearings

Grip-friendly rim

## Dimensions

(small deviations possible)

## Order No. 5.20880

### Scooping Wheel

Diameter	1.20 m
Weight	70 kg

## Order No. 5.42010

### Water Scoop

Height	1.20 m
Length	2.65 m
Width	2.70 m
Weight	130 kg
Flow Dish	
Diameter	0.90 m
Height	0.20 m
Distance between Scooping Wheel and Channel bottom	0.035 m

## Attention:

**Exact measurements may vary; for all installation dimensions refer to current assembly instructions.**

Technical changes reserved.

**For use in aggressive environments such as salt or chlorine water, the equipment is also available in marine grade steel (V4A).**

Safety check according to DIN EN 1176

## Components

### Order No. 5.20880

#### Scooping Wheel

- 1 Scooping Wheel with bearings and alternating water runoff
- 1 Rack

### Order No. 5.42010

#### Water Scoop

- 1 Scooping Wheel with bearings and alternating water runoff
- 1 Rack
- 2 Water Channels
- 1 Flow Dish

## Installation information

Surfacing requirements  
no fall height according to standard

### Recommendation:

- Pavement or a similar surface with a runoff for water
- Water depth: for a proper function a min. water depth of 20 cm is required.
- Water supply and water basin have to be provided for on site.

### Foundations

#### Scooping Wheel


2 items 50 x 30 x 40 cm  
Excavation depth 60 cm

#### Channels


6 items 30 x 30 x 40 cm  
Excavation depth 60 cm

#### Flow Dish

2 items 65 x 30 x 40 cm  
Excavation depth 60 cm



5.20880



5.42010